GENT by Honeywell

6.1: VIGILON CONTROL PANELS

A3 Mimic Panel

TThe A3 mimic panel provides a pictorial representation of a building's layout. This gives a rapid, visual indication of the location of any fire incident.

It can also be used to provide indication of fault and supervisory events in the system.

This one panel can be used as a Zonal Mimic or can hold a pictorial overlay to provide a customised view.

The A3 Customised Mimic panel can be mounted in either landscape or portrait, while an A3 Zonal Mimic panel must only be mounted landscape when using the overlay supplied.



TECHNICAL SPECIFICATION	
Туре	A3 Mimic Panel
Max Quantity per Loop	4
Batteries	2 x 6V @ 7Ah
Battery Standby	24 hours + 30 minutes alarm upgradeable to 72 hours
Approx Weight	7.9 Kg without batteries 10.5 Kg with batteries
Operating Temperature	0°C to 45°C
Cable Entry	Rear
Load Factor	3
Relevant Standard	EN 54 Part 2 & 4
Indicators	1536 Number – High Intesity Red LED's
Approvals	Applied for

ORDER CODES

Mimics and Repeat Panels (EN54)		
Vigilon Repeat Panel 72 hour ((New) BS & EN	
compatible	VIG-RPT-72	
Non-functional LCD Repeat Display (RS485		
connection to panel)	COMPACT-RPT	
A3 Zonal and Graphic Mimic	VIG-MIM-A3	
Repeat Panel and Mimi	ic	
Accessories		
Vigilon Repeat Panel Battery Pa	ack VSRPT-BATT	
Battery Pack for A3 Mimic (2 x	6v 7 Ah)	
	VSRPT-BATT-A3	
Repeat Panel Flush Surround	VIG-RPT-FLUSH	
Stainless Steel Door for Vigilon	Repeat	
V	'IG-RPT-DOOR-SS	
Stainless Steel Repeat Panel Fl	ush Mounting	
Kit V	IG-RPT-FLUSH-SS	
LED Driver Board for Special M	limics	
	S4-34600	

Dimensions (mm)

