

SYNTHETIC HOSE ACCESSORIES



PRODUCT DESCRIPTION:

Adjustable nozzle are used for Class A and B fires in most industrial applications. They are used with lined fire hose. Adjustable fog, straight stream and shut off

PRODUCT FEATURES:

UL Listed

Available sizes: 1 1/2" & 2 1/2"

Adjustable fog, straight stream and shut off

Finish :

Brass and Chrome

Thread: NST/BS336

NST to BS336 male adaptor available if required.

Nozzle pressure: 100 psi

Discharge GPM as in Ullisting



Model No.	Fire Type	Size, in.	Max Inlet Pressure PSIG	Rated Operating Pressure, PSIG	Rated Flow at Rated Operating Pressure, PSIG	Flow in Wide Open Position at 100 PSIG, GPM
Basic Spray Nozzles						
SFD-NH-83-40	Class A and B	1-1/2	200	100	104	104
SFD-NH-65	Class A and B	2-1/2*	200	100	280	280
SFD-NH-40	Class A and B	1-1/2**	200	100	130	130

* Includes both NH (NST) and NPSH (IPT) inlet thread configurations. Also includes BS336 "Morris" instantaneous coupling Inlet configuration.

** Includes both NH (NST) and NPSH (IPT) inlet thread configurations.

PRECAUTIONS:

Use of solid stream from nozzle around electrical apparatus and circuits may involve serious accident hazards and these nozzles, therefore, are not recommended for Class C fires.