

Turbo-Nozzles

AWG-Turbo-Nozzles meet the standard DIN 14 367 for branchpipes. The flow rates can be selected by the adjusting sleeve, and opening and closing by means of the lever. A special feature is the extinguishing power, due to optimal droplet size also at the full range of the 0° to 120° adjustable water-filled spray stream. The AWG-Nozzles have two pointers, a good aid to feel the selected flow rate as well as the type of the stream. With Flash-Over position. Inlet also swivelling under pressure.

Information about the test results and approvals for AWG-Nozzles as well as the possibility to use them on electrical installations is available upon request.

- Aluminium alloys (A)
- Copper alloys (C)

Turbo-Nozzle 2235 / 2950



4310

British Standard BS 336 Connection, Instantaneous

| Inlet swivelling | Type | Flow rate selection l / min at 6 bar | Weight (kg) | Style | Ident-No. | Remarks | Alloy |
|------------------|------|--------------------------------------|-------------|--------|-----------|---------|-------|
| 1 ½" m | 2235 | 60-130-235 | 2,200 | 4300 B | 60584633 | | A |
| 2 ½" m | 2235 | 60-130-235 | 2,430 | 4300 B | 60578833 | | A |
| 2 ½" m | 2400 | 130-135-400 | 2,480 | 4300 C | 60578933 | | A |
| 2 ½" m | 2750 | 360-550-750 | 3,500 | 4300 D | 60618033 | | A |
| 2 ½" m | 2950 | 550-750-950 | 3,500 | 4300 D | 60618133 | | A |